




## BRASS / STAINLESS STEEL SOLENOID VALVE 52 – 53












- Coil size 22
- 2/2 way NC - 2/2 way NO - 3/2 way NC
- Direct acting
- Stainless steel or brass tube
- ED 100%

Technical data			
Body material	Brass		
Seal material	EPDM – NBR - FKM		
Tube material	Stainless steel or brass		
Working fluids	Air, water, steam		
Electrical connect.	6,3 x 0,8 fast-on terminal		
Insulation class	H		
Coil voltage	220-230VAC 50-60Hz	100-120VAC 60Hz	12-24 VDC
Coil power series 55	13,5 VA	14 VA	9 W
Ambient temp. series 55	120 °C	80 °C	80 °C
Fluid temp. series 55	140 °C	145 °C	140 °C
Approvals	VDE; CE	UL	CE

Performance							
<b>2/2 way NC</b> Series 52				<b>3/2way NC</b> Series 53			
Orifice size mm	Flow m3/h	MOPD (bar)		Orifice size mm	Flow m3/h	MOPD (bar)	
		AC	DC			AC	DC
1,6	0,075	25	12	1,0	0,040	20	15
2,0	0,110	17	10	1,5	0,080	11	9
2,8	0,180	4.5	1.5	2,0	0,090	6,5	5,5
				2,5	0,130	4,5	3,5
<b>2/2 way NO</b> Series 52							
Orifice size mm	Flow m3/h	MOPD (bar)					
		AC	DC				
1,4	0,070	20	20				

Note: For pipes and codes see drawings

Hydraulic connection				
2/2 WAY NC		2/2 WAY NO	3/2 WAY NC	
IN/OUT G1/8" Series 5220 (1)	FLANGE (CH 25) Series 5270	IN/OUT G1/8" Series 5201 (2)	IN/OUT G1/8" Series 5320 (1)	FLANGE (CH 25) Series 5370
				
<b>Notes:</b> Food grade nickel treatment available on demand (1): Stainless steel tube (2): Also available with IN quick connection / OUT hose bib connection (Series 5243)				
<b>Availability coil orientation</b> <div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <p>"A" (STANDARD)</p>  </div> <div style="text-align: center;"> <p>"B"</p>  </div> <div style="text-align: center;"> <p>"C"</p>  </div> <div style="text-align: center;"> <p>"D"</p>  </div> </div>				