

BRASS SOLENOID VALVE 66




- Coil size 33mm
- 2/2 way NC - Direct acting
- Cold / high temperature fluids
- Multi purpose usage
- ED 100%

Technical data

Body material	Brass	
Seal material	EPDM – NBR - FPM	
Tube material	Brass	
Working fluids	Air, water, steam	
Electrical connect.	6,3 x 0,8 fast-on terminal	
Insulation class	H	
220-230VAC 50-60Hz Approvals: CE; VDE	Power (VA)	17
	Amb. T. (°C)	120
	Fluid T. (°C)	150
100-120VAC 60Hz Approvals: CE; UL	Power (VA)	22
	Amb. T. (°C)	80
	Fluid T. (°C)	150
12-24 VDC Approvals: CE	Power (W)	16
	Amb. T. (°C)	80
	Fluid T. (°C)	150












Performance



Orifice size * (mm)	Flow (m3/h)	MOPD (bar)	
		AC	DC
2,0	0,085	25	12
3,0	0,170	9	5
4,0	0,390	6	4

*: For pipes and codes see drawings

Hydraulic connection


<p>IN 1/8" – OUT 1/8" Series 6611</p> 	<p>IN 1/4" – OUT 1/4" Series 6610</p> 	<p>IN 1/4" – OUT 1/4" NPT Series 6604 - 6605</p> 	<p>IN 3/8" – OUT 3/8" NPT Series 6606</p> 	<p>IN 1/2" – OUT 1/2" NPT Series 6607</p> 
<p>IN 1/8" – OUT HOSE BIB Series 6622</p> 	<p>IN 1/4" – OUT HOSE BIB Series 6625</p> 	<p>IN 1/8" – OUT HOSE BIB Series 6628</p> 	<p>IN 1/4" – OUT HOSE B. Series 6630</p> 	<p>IN 1/4" – OUT 1/4" + pr.switch Series 6660</p> 
<p>IN 1/2" – OUT 1/4" + man.override Series 6601</p> 				

Notes


Food grade nickel treatment available on demand

Availability coil orientation


"A" (STANDARD)



"B"



"C"



"D"

